

FATHOM E+ 29 2 ELECTRIC BIKE



SPECS

HYBRID CYCLING TECHNOLOGY	
MOTOR	Giant SyncDrive Sport
CONTROLLER	Giant RideControl One ANT+
DISPLAY	Wireless display compatible (ANT+ and Bluetooth)
BATTERY	Giant EnergyPak Smart 500, 36V Integrated Lithium-Ion
FRAME	
SIZES	S, M, L, XL, XXL
COLOURS	Matte Gunmetal Black
FRAME	ALUXX Aluminium, Overdrive 1½ - 1⅝" Head Tube, 141mm Boost QR, ISS, Giant EnergyPak Plus Range Extender Compatible, Integrated KS18 Kickstand Mount, compatible with fenders
FORK	SR Suntour XCR 32 Boost Coil LOR 29 120mm travel, Tapered 1½ - 1⅝" steerer, lockout
SHOCK	N/A
COMPONENTS	
HANDLEBAR	Giant Connect TR Riser 31.8x690-780mm
STEM	Giant Contact
SEATPOST	Giant 30.9mm, 2-bolt Micro Adjustable, Forged Aluminium
SADDLE	Giant Sport
PEDALS	Aluminium Platform
DRIVETRAIN	
SHIFTERS	Shimano Deore
FRONT DERAILLEUR	-
REAR DERAILLEUR	Shimano Deore, 10-Speed, Shadow+
BRAKES	Shimano BR-MT200, hydraulic disc, 180mm [F&R]
BRAKE LEVERS	Shimano BL-MT200
CASSETTE	Shimano CS-M4100-10 11-46T 10-Speed
CHAIN	KMC e.10 Sport, e-bike optimised
CRANKSET	Forged Alloy minimal Q-factor, 36T Steel Direct Mount
BOTTOM BRACKET	N/A
WHEELS	
RIMS	Giant XCT 29 Tubeless Ready 25mm e-bike optimised
HUBS	Giant eTracker Sport, [F] 15mm Thru-Axle [R] 141mm QR, e-bike optimised
SPOKES	Stainless steel
TYRES	Maxxis Rekon 29x2.4", EXO, 60 TPI (max tyre width possible: 2.4" rear, 2.5" front)
EXTRAS	Giant EnergyPak 6A Smart charger, Giant EnergyPak Plus range extender compatible

FEATURES

- Frame: ALUXX Aluminium, Overdrive 1½ - 1⅝" Head Tube, 141mm Boost QR, ISS, Giant EnergyPak Plus Range Extender Compatible, Integrated KS18 Kickstand Mount, compatible with fenders
- Fork: SR Suntour XCR 32 Boost Coil LOR 29 120mm travel, Tapered 1½ - 1⅝" steerer, lockout
- Shifters: Shimano Deore
- Crankset: Forged Alloy minimal Q-factor, 36T Steel Direct Mount
- Colours: Matte Gunmetal Black

Price: €3,279

GEOMETRY

FRAME	S	M	L	XL	XXL
Seat Tube Length (mm)	405	455	505	535	560
Seat Tube Angle	73.0°	73.0°	73.0°	73.0°	73.0°
Top Tube Length (mm)	575	600	625	650	675
Head Tube Length (mm)	105	115	125	140	155
Head Tube Angle	68.0°	68.0°	68.0°	68.0°	68.0°
Fork Rake (mm)	46	46	46	46	46
Trail (mm)	100.7	100.7	100.7	100.7	101
Wheelbase (mm)	1141	1167	1193	1219	1245
Chain Stay Length (mm)	475	475	475	475	475
Bottom Bracket Drop (mm)	45	45	45	45	45
Stack (mm)	625	634	643	657	671
Reach (mm)	384	406	428	449	470
Stand Over Height (mm)	723	753	788	808	828
Handlebar Width (mm)	780	780	780	780	780
Stem Length (mm)	50	60	60	70	70
Crank Length (mm)	165	170	170	170	170
Wheel Size	29"	29"	29"	29"	29"

All specifications listed are subject to change without notice.